



CP-48LR PC Cartridge Replenisher

For Processing Fujicolor Papers in Frontier Minilabs

Catalog Number: 60005482 (125m²)

DESCRIPTION

Developed for use with Fuji Frontier 330, 350, 355, 370, 375 & 390 minilabs. This product is a plug-in replenishment cartridge system that eliminates the need to mix processor replenisher chemicals. Each cartridge contains both developer and bleach fix and is designed to process 125 m² (square meters) of paper.

SAFE HANDLING INSTRUCTIONS

Please refer to Material Safety Data Sheets (MSDS) for specific chemical details. For emergencies, please contact CHEMTREC at 1-800-424-9300. You can obtain an MSDS by calling the Fujifilm Technical Hotline at 1-800-526-0851 Ext. 10.

HMIS INFORMATION

Hazardous Materials Identification System. Please refer to Section 3 in the MSDS for further information.

	Concentrate			Working Tank	
	P1-R	P2-RA	P2-RB	P1	P2
Health	3	2	2	1	1
Flammability	0	0	0	0	0
Reactivity	0	0	0	0	0
Personal Protection	C	C	C	C	C

SHELF LIFE

	Concentrate			Working Tank	
	P1-R	P2-RA	P2-RB	P1	P2
Time	U= 24 Mo	U= 24 Mo	U= 24 Mo	1 Week	1 Week
Color	Clear, Yellow	Clear, Dark Brown	Clear, Pale Yellow	Clear, Pale Yellow	Clear, Pale Yellow
Odor	No Odor	No Odor	Slight Ammonia	No Odor	Slight Ammonia

U = Unopened, O = Opened

SPECS & RECOMMENDATIONS

330/350/3500/370/375/390

Temperature	P1 = 38.5° ± 0.3° C 101.3° ± 0.5° F	
	P2 = 38.0° ± 2.0° C 101.4° ± 3.6° F	
	PS = 35° – 40° C 95° – 104° F	
Processing Time	P1 = 45"	
	P2 = 45"	
PS (4 tanks) = 1'30"		
Starting Replenishment Rate	P1	40 ml/m ²
	P2	31.1 ml/m ²
	PS	With RC-50: 121 ml/m ² Without RC-50: 175 ml/m ²

SPECIFIC GRAVITY & pH

P1	pH @ 25° C	SpG @ 25° C	SpG @ 38.5° C
P1-R Replenisher	12.50 ± 0.10	1.045 ± 0.005	1.039 ± 0.005
P1 Fresh Tank	10.15 ± 0.05	1.045 ± 0.005	1.039 ± 0.005
P1 Seasoned Tank	10.45 ± 0.05	1.055 ± 0.005	1.049 ± 0.005
P2-RA Replenisher	6.10 ± 0.10	1.117 ± 0.010	1.010 ± 0.010
P2-RB Replenisher	5.90 ± 0.10	1.205 ± 0.020	1.198 ± 0.020
P2 Fresh Tank	6.80 ± 0.30	1.080 ± 0.020	1.073 ± 0.020
P2 Seasoned Tank	6.50 ± 0.30	1.110 ± 0.020	1.103 ± 0.020

The data contained in this photographic bulletin is believed to be true and accurate, but is offered solely for your consideration, investigation, and verification. Nothing herein shall be construed to be a warranty or guarantee by either FUJIFILM Hunt Chemicals or any of its affiliates, and all such warranties, implied or otherwise, including any implied warranty of merchantability, are hereby expressly disclaimed. You, of course, are fully responsible for any use and / or domestic or foreign sale of the product(s) described, and nothing in this photographic bulletin shall be construed to constitute permission or a recommendation to practice any invention covered by patent or patent application or know-how owned by FUJIFILM, its affiliates, or others.